



# MONO-FACIAL MODULE N-TYPE 495~510 Watt



**Cutting Free Technology**  
Minimized micro-crack



**Anti-PID (potential induced degradation)**  
Passed anti-PID test under 85% damp heat  
85% relative humidity for 96 hours



**Higher Power Output**  
Lower shading and resistive loss



**Outstanding mechanical load resistance**  
2400 Pa wind load, 5400 Pa snow load



**15-year product warranty**  
**30-year linear power output**



CEC Listed



IEC 61215, IEC 61730  
ISO 9001: 2015 (Quality management systems)  
ISO 14001: 2015 (Environmental management systems)  
ISO 45001: 2018 (Occupational health and safety)  
UNI 9177 Ia CLASSE DI REAZIONE AL FUOCO:1




# TOPCON(N TYPE) 495~510Watt



## ELECTRICAL SPECIFICATIONS

Module Type	UL-495M-120BHVN		UL-500M-120BHVN		UL-505M-120BHVN		UL-510M-120BHVN		
	STC*	NOCT*	STC*	NOCT*	STC*	NOCT*	STC*	NOCT*	
Maximum Power (Pmax)	W	495	375	500	379	505	383	510	386
Maximum Power Voltage (Vmp)	V	36.85	33.90	37.02	34.06	37.18	34.21	37.35	34.36
Maximum Power Current (Imp)	A	13.43	11.06	13.51	11.13	13.58	11.19	13.65	11.25
Open-circuit Voltage (Voc)	V	43.52	39.60	43.78	39.84	43.98	40.02	44.30	40.31
Short-circuit Current (Isc)	A	14.43	11.64	14.48	11.68	14.54	11.73	14.59	11.77
Module Efficiency STC	%	22.36		22.59		22.81		23.04	
Operating Temperature	-40°C~85°C								
Maximum system voltage	DC1500V(IEC)								
Maximum series fuse rating	25A								
Power tolerance	0~+5 Watt								
Temperature coefficients of Pmax	-0.29%/°C								
Temperature coefficients of Voc	-0.250%/°C								
Temperature coefficients of Isc	0.046%/°C								
Nominal operating cell temperature (NOCT)	43±2°C								




\*STC : Cell temperature: 25°C, Irradiance: 1000 W/m², Air mass: 1.5G

\*NOTC : Air temperature: 20°C, Irradiance: 800 W/m², Air mass: 1.5G, Wind speed: 1 m/s


## SPECIFICATIONS

Cell Type	182.2×94mm N type Mono-crystalline
No. of cells	120 (6×10×2)
Dimensions	1952*1134*30mm
Weight	22.5Kg
Front Glass	3.2mm, Anti-Reflection Coating, High Transmission, Low Iron, Tempered Glass
Junction Box	IP68, 3 diodes
Connector	MC4 Compatible
Cable Length (Including Connector)	4mm² Portrait: (+)400 mm/(-) 200mm Landscape: (+) 1200mm/(-)1200 mm
Packaging Configuration	Two Box=One pallet 36pcs/Box, 72pcs/Pallet, 864pcs/40HQ Container



## I-V CURVE[500W]

I-V characteristics at different irradiances



I-V characteristics at different temperature

