

EzLogger Pro

EzLogger Pro is a self-developed monitoring device by GoodWe. In combination with a GoodWe solar inverter, it can easily read and record all key plant data and constantly transmit the data to the GoodWe portal via internet.



Communication distance up to 1000m



Connectivity for up to 60 devices at once



Data Breakpoint Resume



Encrypted Data Transmission Process

Model	Ezlogger Pro
Device Management	
Max. Number of Connected Devices	60
Electrical	
AC Power Supply	100 ~ 240V, 50 / 60Hz
DC Power Supply	12V
Power Consumption (W)	<6
Communication Interface	
LAN	1
PLC	0
RS485	COM x 4
Digital / Analog Input / Output	DI x 4
Communication Protocol	
Ethernet	IEC 60870-5-104
RS485	Modbus-RTU
User Interface	
LED	LED x 8
USB	USB 2.0 x 1
Mechanical	
Dimensions (W x H x D mm)	190 x 118 x 37
Weight (kg)	0.5
Installation Method	Wall Mounting, DIN Rail Mounting, Tabletop Mounting
Environment	
Operating Temperature Range (°C / °F)	-20 ~ +60
Storage Temperature Range (°C / °F)	-40 ~ +70
Relative Humidity	5 ~ 95%
Max. Operating Altitude (m / ft)	2000
Ingress Protection Rating	IP20

*: Please visit GoodWe website for the latest certificates.